

AC/DC Current Probe

TCP0030 Data Sheet



Features & Benefits

- Easy-to-use and Accurate AC/DC Current Measurements
- Connects Directly to DPO7000 and DPO4000 Series Oscilloscopes Using the New TekVPI™ Probe Interface
- Provides Automatic Units Scaling and Readout on the Oscilloscope Display
- Split-core Construction Allows Easy Circuit Connection
- DC to >120 MHz Bandwidth
- 30 A RMS Maximum Current Capability
- 50 A Peak Pulse Current Capability

- High Accuracy with Typically Less than 1% DC Gain Error
- Accurately Measures Current Levels as Low as 1 mA
- Low Noise and DC Drift
- Easy to Degauss and Autozero
- Setup Controls and Probe Status/Diagnostic Indicators are Provided on Both the Probe Hardware, and through an Easy-to-Access Oscilloscope UI Display Menu
- Safety Certified for U.S. and Canada

Applications

- Power Supplies
- Semiconductor Devices
- Power Inverters/Converters
- Electronic Ballasts
- Industrial/Consumer Electronics
- Mobile Communications
- Motor Drives
- Transportation Systems

TCP0030

TCP0030 is a high-performance, easy-to-use AC/DC current probe designed for use and direct connection (without the need of an additional power supply) to the TekVPI™ probe interface used on Tektronix' new DPO7000 and DPO4000 Series Oscilloscopes. This AC/DC current measurement probe provides greater than 120 MHz of bandwidth with selectable 5 A and 30 A measurement ranges. It also provides exceptional low-current measurement capability and accuracy to current levels as low as 1 mA, important for meeting today's challenging current measurement needs.

Characteristics

Bandwidth – DC to ≥ 120 MHz

Rise Time – ≤ 2.92 ns

Max RMS Current – 30 A

Max Peak Pulse Current – 50 A

Minimum Sensitivity –

1 mA (on oscilloscopes that support 1 mV/div setting)

AC Coupling (on oscilloscopes that support AC/DC coupling)

Current Ranges – 5 A and 30 A

Max Bare-wire Voltage – Use insulated wire only

Typical Characteristics

DC Accuracy –

$\pm 1\%$ typical

$\pm 3\%$ warranted

Max Amp-second Product – 500 A* μ s (in 30 A Range)

Insertion Impedance –

1 m Ω at 10 kHz

3.5 m Ω at 100 kHz

0.08 Ω at 1 MHz

0.15 Ω at 10 MHz

0.7 Ω at 100 MHz

0.85 Ω at 120 MHz

Signal Delay – 14.5 ns

Environmental

Temperature –

Operating: 0 °C to +50 °C

Nonoperating: -40 °C to +75 °C

Humidity –

Operating: 5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above 30 °C up to +50 °C, noncondensing

Nonoperating: 5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above 30 °C up to +75 °C, noncondensing

Altitude –

Operating: Up to 3,000 m (10,000 ft.)

Nonoperating: Up to 12,192 m (40,000 ft.)

Regulatory

Compliance Labeling –

CE (European Union)

WEEE (European Union)

Physical Characteristics

Probe Head Size	cm	in.
Height	3.2	1.25
Width	1.6	0.625
Length	20	7.77

Other Dimensions

Cable Length	200	79
Max Conductor Diameter	0.38	0.15

Weight	kg	lb.
Shipping	1.55	3.44

Power Requirements

TCP0030 is powered directly by the DPO7000 and DPO4000 Series Oscilloscopes using TekVPI™ interface

Recommended Oscilloscopes

DPO7000 and DPO4000 Series Oscilloscopes with TekVPI™ probe interface.

Standard Warranty

One year parts and labor.

Ordering Information

TCP0030

AC/DC Current Probe

Includes: Instruction manual (071-1812-xx English, or 071-1813-xx Japanese, or 071-1814-xx Simplified Chinese)*1, Protective Cover (016-1923-xx), Probe Ground Lead – 6 in. length (196-3120-xx), Nylon Carrying Case (016-1952-xx).

*1 Specify manual language when ordering.

Language Options

Opt. L5 – Japanese instruction manual.

Opt. L7 – Simplified Chinese instruction manual.

Service Options

Opt. C3 – Calibration Service 3 Years.

Opt. C5 – Calibration Service 5 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Recommended Accessories

Current Loop, 1 Turn, 50 Ω with BNC connector used for Performance Verification – Order 015-0601-50.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

Contact Tektronix:

- ASEAN / Australasia** (65) 6356 3900
- Austria** 00800 2255 4835*
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 00800 2255 4835*
- Brazil** +55 (11) 3759 7627
- Canada** 1 800 833 9200
- Central East Europe and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** 00800 2255 4835*
- Germany** 00800 2255 4835*
- Hong Kong** 400 820 5835
- India** 000 800 650 1835
- Italy** 00800 2255 4835*
- Japan** 81 (3) 6714 3010
- Luxembourg** +41 52 675 3777
- Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 00800 2255 4835*
- Norway** 800 16098
- People's Republic of China** 400 820 5835
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 001 800 8255 2835
- Russia & CIS** +7 (495) 7484900
- South Africa** +41 52 675 3777
- Spain** 00800 2255 4835*
- Sweden** 00800 2255 4835*
- Switzerland** 00800 2255 4835*
- Taiwan** 886 (2) 2722 9622
- United Kingdom & Ireland** 00800 2255 4835*
- USA** 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

02 Oct 2011

51W-19042-2

